



**Compuprint 9080** offers an unbeatable print performance level thanks to improved electronic and mechanical solutions

# Compuprint 9080

660 Page per Hour  
330 Lines per Minute  
800 Million Characters Print Head Life

These print performance with eight copies capability, dual tractors, wide range of barcodes, macrocharacters, ease of use, emulations, interfaces and global reliability make the **Compuprint 9080 the ideal choice.**



### Value and Features

- 24 pins print-head with 800 Million Characters life
- 660 Pages Per Hour (PPH)
- 330 Lines Per Minute (LPM)
- Superior performance in graphics printing
- Dual front straight paper paths
- Up to 8 copies capability
- Simple to use, pre-set configurations
- Parallel, Serial, USB 2.0 and LAN interfaces
- Wide range of barcodes and macro-characters

### A leading-edge series for today and tomorrow

Compuprint 9080 integrates the latest technology and innovation based on more than 30 years of Compuprint leadership in the serial printer technology. It represents the preferred choice for business and industrial printing applications requiring up to 57,000 (\*) pages per month workload, providing the best investment.

### Fast, flexible, reliable

Compuprint 9080 is built on state-of-the art technologies and innovative functionalities. It provides reliable continuous paper paths with two front 4 pins tractors equipped with paper run sensors, automatic paper path alternance, paper thickness recognition, paper parking/loading and zero tear off. All with the superb reliability of 20.000 hours of MTBF.

### For a broad range of connectivity and printing requirements

The Compuprint 9080 is available with different interface configurations: Parallel/Serial/USB or Parallel/LAN. With the LAN configuration is possible to manage the printer from remote by the NetViewMaster software or the embedded WEB Page. A large number of character set, fonts and barcodes combined with a set of emulation and protocols allow to use the printer in most environments and to be the ideal solution for industrial requirements for printing macro characters, barcodes on statements, labels and pre-printed forms.

<b>Printing Technology</b>	24 pin serial dot matrix printer - 136 columns @ 10 cpi				
<b>Real Throughput (note 1)</b>	<b>Char. per line</b>	40	80	136	
	<b>LPM</b>	450	330	250	<b>ISO/IEC 10561 PPH</b>
					<b>DIN Letter 10cpi</b> 660
					<b>Spreadsheet 10cpi</b> 450
<b>Printing speed (cps)</b>	<b>10 cpi</b>	<b>12 cpi</b>	<b>15 cpi</b>		
	HSD	900			
	Draft	800	960	1200	
	Best Draft	400	480	600	
	NLQ	267	320	400	
	LQ	133	160	200	
<b>Paper handling</b>	Continuous form: front loading - Fanfold width 76 to 432 mm (3 to 17 inches) Front push tractor 6 pin (BASE CONFIGURATION) Additional front push tractor 6 pin (optional)				
<b>Copies</b>	1 + 7 - max thickness 0,635 mm (0,025 inches)				
<b>Special functions</b>	Automatic paper path switching via operator panel or SW commands Automatic Gap Adjustment (AGA) of print head based on paper thickness Automatic fanfold positioning (zero tear-off) Automatic paper parking of continuous form				
<b>Graphic resolution (dpi)</b>	60, 80, 90, 120, 180, 240, 360 (horizontal) 60,72, 180, 360 (vertical)				
<b>Vertical spacing</b>	6 - 8 - 12 lines per inch; 3 - 4 - 6 - 8 - 12 lines per 30 mm.; n/60, n/72, n/180, n/216, n/360 per inch				
<b>Horizontal spacing</b>	10, 12, 15, 17.1, 20 cpi and proportional				
<b>Barcodes</b>	UPC/A, UPC/E, EAN8, EAN13 - UPC/EAN ADD-ON 5, UPC/EAN ADD-ON 2 - Code 39 - Code 128 - Code 11- Code 93 - MSI - Postnet - Codabar - 2/5 Interleaved -2/5 Matrix - 2/5 Industrial - Code GP - C25-3BAR - Code BCD - 2/5 Bidirectional				
<b>Character set</b>	<b>Standard PC IBM character sets:</b> CS1, CS2 ; 13 EPSON national variations <b>IBM and EPSON character sets:</b> CP 437 (USA), CP437G (Greek), CP437SL (Slavic), CP850 (Multilingual), CP851 (Greek), CP852 (Eastern Europe), CP853 (Turkish), CP855 (Cyrillic), CP857 (Turkish), CP858 (Euro PC Multilingual), CP860 (Portugal), CP862 (Hebrew), CP863 (French-Canadian), CP864 (Arabic), CP865 (Danish-Norwegian), CP866 (Russian), CP867 (Turkish2), CP876 (OCR-A), CP877 (OCR-B), CP1098 (Farsi), CP1250 (Latin2 Windows), CP1251 (Cyrillic Windows), CP1252 (Latin1 Windows), CP1253 (Greek Windows), CP1254 (Turkish Windows), CP1255 (Hebrew Windows), CP1256 (Arabic Windows), CP1257 (Baltic Windows), 96Greek, GOST, TASS, MAZOWIA, KOI8-U, UKRANIAN, Farsi 1, Farsi 2 <b>ISO character sets:</b> 8859/1 (Latin1), 8859/2 (Latin2), 8859/3 (Latin3), 8859/4 (Latin4), 8859/5 (Latin/Cyrillic), 8859/6 (Latin/Arabic), 8859/7 (Latin/Greek), 8859/8 (Latin/Hebrew), 8859/9 (Latin5), 8859/15 (Latin9) <b>DEC PPL2 character sets</b>				
<b>Resident font</b>	Draft, Courier, Gothic, Prestige, Present, Script, OCR-A, OCR-B				
<b>Resident Emulations</b>	Epson ® ESC/P LQ Series, IBM ® Proprinter XL24, IBM ® Personal Printer 2391, ANSI, DEC PPL2, Compuprint native commands				
<b>Interfaces</b>	Parallel - Ethernet 10/100 or Parallel - Serial - USB 2.0      Input buffer up to 128 Kbytes - Plug&play (Windows environment)				
<b>Drivers and Sw</b>	Windows 9X/2000/XP/Vista NetViewMaster (remote printer management SW) and Internal WEB Page (both available with LAN interface)				
<b>Reliability</b>	<b>MTBF:</b> 20.000 hours				
<b>Print Head Life</b>	800 Millions Characters				
<b>Ribbon life</b>	Black Long Life ribbon 25 Millions Characters				
<b>Noise Level</b>	54 dBA				
<b>Power Supply</b>	<b>Tension:</b> 100V - 240V <b>Frequency:</b> 60 Hz - 50 Hz				
<b>Power consumption</b>	116W Max. (printing), 22W (standby)				
<b>Physical Dimensions &amp; Weight</b>	670 (W) x 320 (H) x 390 (D) mm - 21 Kg				



www.profiprint.cz  
Tel.: +420 541 241 957  
Email: profiprint@profiprint.cz



Ordering Information

### Printers and Supplies

Compuprint 9080- Par/Ser/USB	PRTN980
Compuprint 9080- Par/Lan	PRTN980N
Black ribbon 25 MC	PRKN102-1

### Options

Additional tractor	PRFN2TR6
Open pedestal	PRFN-PD1
Controller Interface Par/Ser/USB	PRAN980
Controller Interface Par/Lan	PRAN980N

Note 1 - The Compuprint 9080 measured performance herein declared are superior than any other competitive serial matrix printer model

The information contained in this document is subject to change without notice. All company and product names mentioned herein are trademarks or registered trademarks of their respective owners.  
Copyright © 2008 Sferal wwt