



The **fastest** Serial Printer today available in the Printing World

Compuprint 9300 adopts enhanced and improved electronic and mechanical solutions that move the real print performance to an unbeatable level

860 Page per Hour
460 Lines per Minute
800 Million Characters Print Head Life

Compuprint 9300

The combination of such print performance with eight copies capability, dual tractors, wide range of barcodes, macrocharacters, ease of use, emulations, interfaces and the extraordinary global reliability make the **Compuprint 9300 simply unique**

Value and Features

- 18 pins print-head with 800 Million Characters life
- 860 Pages Per Hour (PPH)
- 460 Lines Per Minute (LPM)
- Superior performance in volume printing
- Dual front straight paper paths
- Up to 8 copies capability
- Simple to use, pre-set configurations
- Wide range of barcodes and macro-characters
- Parallel, Serial, USB 2.0, LAN or IPDS-LAN interfaces



A leading-edge printer for today and tomorrow

Compuprint 9300 integrates the latest technology and innovation based on more than 30 years of Compuprint leadership in the serial printer technology. It represents the preferred choice for business and industrial printing applications requiring up to 75.000 (*) pages per month workload.

Fast, flexible, reliable

The Compuprint 9300 is designed with state-of-the art technologies and innovative functionalities. It provides two front continuous paper paths with 6 pins tractors equipped with paper run sensors, automatic paper path alternance, paper thickness recognition, paper parking/loading and zero tear off. All with the superb reliability of 20.000 hours of MTBF.

For a broad range of connectivity and printing requirements

The Compuprint 9300 is available with different interface configurations, Parallel/USB/Serial or Parallel/LAN. Optionally is available the IPDS over LAN interface for OS/400 environments. A large number of character sets, fonts and barcodes combined with a wide set of protocols allow to use the printer in most contemporary environments and to be the ideal solution for industrial requirements for printing macro characters, barcodes on statements, labels and pre-printed forms.



(*) 4 hours a day for 22 days month.

Printing Technology	18 pin serial dot matrix printer - 136 columns @ 10 cpi					
Real Throughput (note 1)	Char. per line	40	80	136	DIN Letter 10cpi	Spreadsheet 10cpi
	LPM	620	460	325	ISO/IEC 10561 PPH	860
Printing speed (cps)		10 cpi	12 cpi	15 cpi		
	HSD	1300				
	Draft	950	1100	1100		
	Best Draft	480	480	480		
	LQ	240	240	240		
Max printing speed (cps)	1600 (correlated to throughput data - compared with competition)					
Paper handling	Continuous form: front loading - Fanfold width 76 to 432 mm (3 to 17 inches) Front push tractor 6 pin (BASE CONFIGURATION) Additional front push tractor 6 pin (optional)					
Copies	1 + 7 - max thickness 0,635 mm (0,025 inches)					
Special functions	Automatic paper path switching via operator panel or SW commands Automatic Gap Adjustment (AGA) of print head based on paper thickness Automatic fanfold positioning (zero tear-off) Automatic paper parking of continuous form					
Graphic resolution (dpi)	60, 72, 80, 90, 120, 144, 240 (horizontal) 72, 144 (vertical)					
Vertical spacing	6 - 8 - 12 lines per inch; 3 - 4 - 6 - 8 - 12 lines per 30 mm.; n/72, n/144, n/216 per inch					
Horizontal spacing	10, 12, 15, 17.1, 20 cpi and proportional					
Barcodes	UPC/A, UPC/E, EAN8, EAN13 - UPC/EAN ADD-ON 5, UPC/EAN ADD-ON 2 - Code 39 - Code 128 - Code 11- Code 93 - MSI - Postnet - Codabar - 2/5 Interleaved - 2/5 Matrix - 2/5 Industrial - Code GP - C25-3BAR - Code BCD - 2/5 Bidirectional					
Character set	Standard PC IBM character sets: CS1, CS2 ; 13 EPSON national variations IBM and EPSON character sets: CP 437 (USA), CP437G (Greek), CP437SL (Slavic), CP850 (Multilingual), CP851 (Greek), CP852 (Eastern Europe), CP853 (Turkish), CP855 (Cyrillic), CP857 (Turkish), CP858 (Euro PC Multilingual), CP860 (Portugal), CP862 (Hebrew), CP863 (French-Canadian), CP864 (Arabic), CP865 (Danish-Norwegian), CP866 (Russian), CP867 (Turkish2), CP876 (OCR-A), CP877 (OCR-B), CP1098 (Farsi), CP1250 (Latin2 Windows), CP1251 (Cyrillic Windows), CP1252 (Latin1 Windows), CP1253 (Greek Windows), CP1254 (Turkish Windows), CP1255 (Hebrew Windows), CP1256 (Arabic Windows), CP1257 (Baltic Windows), 96Greek, GOST, TASS, MAZOWIA, KOI8-U, UKRANIAN, Farsi 1, Farsi 2 ISO character sets: 8859/1 (Latin1), 8859/2 (Latin2), 8859/3 (Latin3), 8859/4 (Latin4), 8859/5 (Latin/Cyrillic), 8859/6 (Latin/Arabic), 8859/7 (Latin/Greek), 8859/8 (Latin/Hebrew), 8859/9 (Latin5), 8859/15 (Latin9) Draft, Courier, Gothic, DP Text, OCR-A, OCR-B					
Resident font	Epson ® FX Series, IBM ® Proprinter III XL, IBM ® Personal Printer 2381, ANSI, Compuprint native commands					
Resident Emulations	Parallel - Ethernet 10/100 or Parallel - Serial - USB 2.0 or Parallel - LAN/IPDS					
Interfaces	Input buffer up to 128 Kbytes - Plug&play (Windows environment)					
Drivers and Sw	Windows 9X/2000/XP/Vista NetViewMaster (remote printer management SW) and Internal WEB Page (both available with LAN interface)					
Reliability	MTBF: 20.000 hours					
Print Head Life	800 Millions Characters					
Ribbon life	Black Long life ribbon 25 Millions Characters					
Noise Level	54 dBA					
Power Supply	Tension: 100V - 240V Frequency: 60 Hz - 50 Hz					
Power consumption	120 W Max. (printing), 30 W (standby)					
Physical Dimensions & Weight	670 (W) x 320 (H) x 390 (D) mm - 21 Kg					



www.profiprint.cz
Tel.: +420 541 241 957
Email: profiprint@profiprint.cz



Ordering Information

Printers and Supplies

Compuprint 9300 - Par/Ser/USB	PRTN9300
Compuprint 9300 - Par/Lan	PRTN9300N
Compuprint 9300 - Par/Lan-IPDS	PRTN9300I
Black ribbon 25MC	PRKN102-1

Options

Additional tractor	PRFN2TR6
Open pedestal	PRFN-PD1
Controller Interface Par/Ser/USB	PRAN930
Controller Interface Par/Lan	PRAN930N
Controller Interface Par/Lan-IPDS	PRAN930I

Note 1 - The Compuprint 9300 measured performance herein declared are superior than any other competitive serial matrix printer model

The information contained in this document is subject to change without notice. All company and product names mentioned herein are trademarks or registered trademarks of their respective owners.
Copyright © 2008 Sferal wwt